

## **RED LINE FULL SYNTHETIC MULTI-VEHICLE CVT FLUID**

Red Line Full Synthetic Multi-Vehicle CVT Fluid is specifically designed and formulated to meet performance requirements and specifications of Continuously Variable Transmissions (CVT).

### **Applications**

- Suitable for use in all CVT applications (belt type and chain driven)
- Step Type Transmissions
- When used in Honda applications, 20,000 mile service intervals are recommended

### **Features/Benefits**

- Optimized for excellent metal to metal friction performance
- Provides advance wear protection, anti-shudder performance, and oxidation stability
- Excellent low temperature fluidity for proper operation in cold weather conditions
- Protects against sludge and varnish
- Helps ensure proper performance and operation of CVT
- Red Line Service Chemical Limited Lifetime Warranty Program coverage (if used every 30,000 miles)

### **Recommended Service Procedure**

- For use in CVT service fill or top off applications
- Consult vehicle's owners manual for OEM service intervals and fluid capacity
- DO NOT OVERFILL

Typical Properties	
Specific Gravity @ 60 °F	0.85
Density, lbs/gal. @ 60 °F	7.05
Vis @ 100°C, cSt	7.8
Vis @ 40°C, cSt	37.7
Viscosity Index	185
CCS Viscosity, Poise, @ °C	55@-35
Flash Point, COC, °C	241
Pour Point, °C	-45
Zinc, wt%	<0.001

## Health Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via [REDLINECHEMICALS.COM](http://REDLINECHEMICALS.COM).